



# ULTRAVIOLET-INFRARED FLAME DETECTOR

## Omniguard® model 860

The Omniguard® model 860 UV/IR flame detector is designed to detect unwanted fires, and output appropriate alarm information. The model 860 senses ultraviolet radiation and infrared radiation in the appropriate wavelengths for very early fire detection. And, using the patented Fire Event Analysis algorithm, is also able to distinguish between real fire and non-fire events providing superior false alarm immunity. The technology has proven itself over decades of reliable service.

The model 860 is available in two versions, one for hydrocarbon fires only, and one for hydrocarbon and certain non-hydrocarbon fires. This dual capability provides the unique capability of providing fire detection for a broad range of fuels with a single unit. Both versions are available with an automatic self-test function to monitor the detector's ability to sense fires, and report a fault condition when impaired.



Typical applications: aircraft hangars, fuel transfer stations, compressor stations, silane storage bunkers, paint spray booths and gas cabinets.

### Key features

- ✧ Patented Fire Event Analysis (FEA) algorithm for superior false-alarm immunity
- ✧ All inclusive three-year warranty on parts and labor
- ✧ Widest field of view in the industry (120°)
- ✧ Robust weatherproof enclosure for indoor or outdoor applications
- ✧ FM, CSA, IECEx and ATEX approved
- ✧ User selectable sensitivities
- ✧ Improved, advanced through-the-lens diagnostic self-test
- ✧ Long range detection
- ✧ Self-contained, explosion-proof enclosure
- ✧ Economical no-test version available
- ✧ Field configurable relays and sensitivity
- ✧ State-of-the-art microprocessor control with proprietary fire library
- ✧ High intensity, localized indication of fire or fault

### Specifications

#### Performance ratings

Responsive to hydrocarbon (gasoline, propane, methane, alcohol, JP-4, JP-3, etc). Also responsive to non-hydrocarbon (hydrogen, silane, hydrazine, etc) flames when special dual-pass IR sensor is used.

Third-party performance certified to detect:


- Saturating signal source in 50 milliseconds
- 1 square foot gasoline fire at 50 feet in 1 second
- 4 square foot aviation fuel fire at 100 feet in 5 seconds or less
- 100 square foot aviation fuel fire at 150 feet in 5 seconds or less
- Methane plume flame at 35 feet in 1 second

Additional performance with dual-pass infrared sensor:

- Silane plume flame 24 inches at 35 feet in 60 milliseconds
- Hydrogen plume flame 20 inches at 35 feet in 3 seconds
- Hydrazine 8 inch pool fire at 80 feet in 9.4 seconds

#### Environmental ratings

Rated:

Class I, Division 1, Groups B, C & D (explosion proof)  
Class II, Division 1, Groups E, F & G (dust ignition proof)  
TYPE 4X weatherproof, dust-tight, watertight  
CE008  II 2 G/D  
Ex d IIB + H<sub>2</sub> T5 Gb for gas  
Ex tb IIIC T100°C Db IP6X for dust

Standard housing is copper-free aluminium conversion coated to MIL-C-5541C, Class 3 (white).  
Optional stainless steel housing available with passive finish per MIL-5-5002C, Type 1.

# Omniguard® model 860

## Specifications (continued)

Standard operating temperature range:  
-40° to +85°C (-40° to +185°F)

### Spectral response

#### Ultraviolet

- Peak sensitivities of 0,22 µm

#### Infrared

- Standard: peak sensitivities of 4.4 µm
- Dual pass: peak sensitivities of 2.9 µm and 4.4 µm

### Detector inputs

#### Inputs

- nominal voltage 24 VDC (ripple voltage <240mV)
- range 20 to 30 VDC

#### Power consumption

- standby 90 mA
- alarm 110 mA
- auto and manual test 250 mA

### Detector outputs

#### Relay

- relays (2) fire, trouble, dry contacts, hermetically sealed
- rated 2 A at 28 VDC. User selects NO or NC
- fire relay user selects latching or non-latching

Current loop (standard version): 0 to 20 mA output

- 20 mA = fire
- 16 mA = UV or IR presence
- 4 mA = ready
- 0 mA = 20

Programmable RS-485 serial output.

### Mechanical considerations

- Weight 2.4 kg (5 lbs) (aluminum)  
6.3 kg (13 lbs) (stainless steel)
- Height x width x depth 114 x 140 x 153 mm  
(4.5 x 5.5 x 6.0 in)
- Conduit entry 3/4-14 NPTF or M20-1.5

### Optional accessories

- Swivel mount No 20856 (used with aluminum)  
No 70991 (used with stainless steel)
- Portable test unit Model 540 / 545
- Air shield assy kit No 8001023
- Rain shield No 23546

## Ordering information

### To order, please specify

Type	Omniguard® model 860
Designation	Ultraviolet-infrared flame detector
Ordering number	860 - X X X O O
Fire type	0 Hydrocarbon 1 Hydrocarbon/non-hydrocarbon
Housing material/conduit entry	0 aluminium, 3/4-14 NPT (white) 2 stainless steel, 3/4-14 NPT 3 aluminium, M20-1.5 (white) 5 stainless steel, M20-1.5
Test feature	0 no self-test 1 auto self-test
Fire relay configuration	
Agency approvals	Factory Mutual (FM) ATEX Canadian Standards Association (CSA) California State Fire Marshall (CSFM) IECEX

