

## OI-315-X Single Gas Personal Monitor

### Single Gas Portable Monitor

The Otis Instruments OI-315 TOCSIN3 Personal Monitor is a versatile personal safety device designed to detect the presence of toxic gases in ambient air. When activated, TOCSIN3 detects the presence of O<sub>2</sub>, CO, SO<sub>2</sub>, H<sub>2</sub>, H<sub>2</sub>S or NH<sub>3</sub>, and alerts the user with visual, vibrating and audible alarms. Features a belt clip that allows it to be conveniently worn on personnel in the field at all times.

Gas Type	Range	T <sub>90</sub>
O <sub>2</sub>	0-30%	< 15 Secs.
CO	0-500 ppm	< 30 Secs.
SO <sub>2</sub>	0-20 ppm	< 35 Secs.
H <sub>2</sub>	0-1000 ppm	< 75 Secs.
H <sub>2</sub> S	0-100 ppm	< 30 Secs.
NH <sub>3</sub>	0-100 ppm	< 60 Secs.



### Product Features

- Polycarbonate Enclosure with Rubber Covering for Shock Protection
- IP67 Water and Dust Proof Rating
- High Performance Audible, Visual and Vibration Alarms
- LCD Display with an LED Back Light
- Automatic System Diagnostics
- Internal Data-Logging for up to 20 Events
- ATEX Intrinsic Safety Certification
- Adjustable Alarm Set-Points
- Battery Life: 1.2 Years or 8 Hours of Use per Day
- User-Replaceable Sensor Element and Battery
- Operating Humidity Range of 5% to 95% RH (Non-Condensing)
- Battery Warranty is 90 Days from Product Ship Date
- 2-Year Limited Hardware Warranty

### OI-315-X Product Specifications

Product Specifications	
Sensor Type	Electrochemical
Operating Power	CR2 Lithium Battery (3V)
Battery Life	1.2 Years or 8 Hours of Use per Day
Measuring Type	Diffusion
Parameter Control	Front 2 Switch (Calibration, Maintenance, Alarm Setting)
Operation Mode Display	Visual: Digital LCD Display, Trouble Red LED
Programmable Set Mode	Alarm Value (1, 2 Alarm) Time Set Calibration Density Setting
Alarm Display	Visual: Alarm and Status Icon, Trouble Red LED Audible: Buzzer
Measuring Value Display	3-Digit LCD Display
T <sub>amb</sub> Temperature Range	-20°C to +50°C (-4°F to 122°F)
Alarm Level Set	Programmable with Detection Range
Internal Data Log	Event Log: 20 Data
Hazardous Location Certification and Approvals	Ex ia IIC T4 IP67 (KGS, ATEX)
Mounting Type	Belt Clip
Operating Humidity	5% to 95% RH (Non-Condensing)
Enclosure Material	Rubber Polycarbonate/TPE
LCD Size	27 W x 17.5 H mm (1.06 in. W x 3.58 in. H x 1.65 in. D)
Product Dimensions	54 W x 91 H x 42 D mm (2.13 in. W x 3.58 in. H x 1.65 in. D)
Weight	120 g (Including Battery)
Hardware Warranty	2-Year, Limited
Part Number Formula	OI-315-[Gas] OI-315-X