

GEN²

OI-6400-X-X Quad Sensor Assembly

Non-Explosion Proof Wired Power Ambient Air Quad Gas Detector

The Otis Instruments OI-6400 Series Ambient Air Quad Gas Detector is a versatile assembly that uses four electrochemical, infrared, PID, or a variety of each, sensor elements to detect a variety of gases. Wired power (12 to 35 VDC) with 4-20mA analog and RS-485 Modbus outputs per each control board.

The OI-6400 includes an AC Power Supply with 6 foot cord to allow for quick installation and power-up.

The OI-6400 also includes a top mounted strobe light and bottom mounted miniature buzzer to alert when any control board is detecting gas above alarm levels. The strobe light can be Red, Amber, or Blue. The Remote Sensor Kit version includes 4 remoted sensor housings with 50 feet of cable per housing.

When the Remote Sensor Kit version is selected the OI-6400 is DC powered by a 25 foot cable and battery clips.



Gas Type	Range	T ₉₀	Warranty
EC-CL2	0-10 ppm	< 60 sec.	12 months
EC-CLO2	0-1 ppm	< 120 sec.	12 months
EC-CO	0-1000 ppm	< 30 sec.	24 months
IR-CO2	0-5% vol.	< 30 sec.	60 months
EC-H2	0-4% vol.	< 60 sec.	18 months
EC-H2S	0-100 ppm	< 30 sec.	24 months
EC-H2S2K	0-2000 ppm	< 25 sec.	24 months
EC-HCL	0-30 ppm	< 300 sec.	12 months
EC-HCN	0-50 ppm	< 70 sec.	12 months
IR-LEL	0-100% LEL	< 30 sec.	60 months
EC-NH3	0-100 ppm	< 90 sec.	12 months
EC-NH3300	0-300 ppm	< 120 sec.	12 months
EC-NH3A	0-1000 ppm	< 120 sec.	12 months
EC-NO2	0-20 ppm	< 25 sec.	12 months
EC-O2	0-25% vol.	< 15 sec.	24 months
EC-PH3	0-5 ppm	< 30 sec.	12 months
EC-SO2	0-20 ppm	< 35 sec.	24 months
PID-VOC10	0-10 ppm	< 3 sec.	6 months
PID-VOC20	0-20 ppm	< 3 sec.	6 months
PID-VOC50	0-50 ppm	< 3 sec.	6 months
PID-VOC1K	0-1000 ppm	< 3 sec.	6 months
PID-VOC2K	0-2000 ppm	< 3 sec.	6 months

Product Features

- Four Electrochemical, Infrared, PID or a Variety of Each Sensor Elements
- AC Power Supply with 6 Foot Power Cord Included (Standard Version Only)
- Operating Temperature Range of -20°C to +54°C
- Graphical LCD with LED Backlight
- Red, Amber, or Blue Strobe Light Mounted on Top
- Dual Tone Buzzer Mounted on Bottom
- 3 Push-Button Interface (ADD, MENU, SUB) per Control Board
- 2 Individually Configurable Alarm Set-Points per Control Board
 - 2 Front Panel LED Indicators (Amber and Red) per Control Board
- Output Options per Control Board:
 - 4-20 mA (3-Wire) Analog
 - RS-485 Modbus
- 1-Year Limited Hardware Warranty
- Sensor Element Warranty Subject to Otis Verification
- Optional Remote Sensor Kit Version



OI-6400-X-X Quad Sensor Assembly

Non-Explosion Proof Wired Power Ambient Air Quad Gas Detector

OI-6400-X-X Product Specifications		
Sensor Types	Electrochemical, Infrared, Photo Ionization Detector	
Power Voltage	AC Power Supply Input Voltage 100-240VAC	
DC Power Draw	2 Amps Maximum at 24VDC	
Protection	Power Electromagnetic Interference (EMI) Filter 4-20 mA Surge Suppression RS-485 Surge Suppression	
Display Screen	Four 102x64 Resolution Graphical LCD Screens with LED Backlights	
Interface	3 Push-Buttons (MENU, ADD, and SUB) per Control Board	
Customizable Settings	2 Individually-Configurable Alarm LED Set-Points (per Control Board)	
Built In Alarms	Red, Amber, Blue or LED Tri-Light Strobe Light Miniature Dual Tone Buzzer	
T _{amb} Temperature Range	-20°C to +54°C / -4°F to 130°F	
Wired (Analog) Output	4-20 mA (3-Wire) & Fault Terminal (per Control Board)	
(Digital) Output	RS-485 Modbus (per Control Board)	
Product Dimensions	17 5/16" T x 10 1/16" W x 6 5/16" D	
Total Weight	11 Lbs	
Hardware Warranty	Limited one year	
Sensor Element Warranties	Varies with Gas Type, Subject to Otis Verification	
Part Number Formula	OI-6400-[Strobe Color]-[Remote Sensor Kit]	
	Strobe Color Options R —Red Strobe Light A —Amber Strobe Light B —Blue Strobe Light	Remote Sensor Kit Option X —No Remote Sensor Kit RSK —4 Remote Sensor Assemblies, Each Remote Sensor Assembly is 50 Feet in length. OI-6400 is DC Powered Using Battery Clips.

